




NTN DRIVESHAFT ANDERSON, INC.



40,000 mm x 68,000 mm x 15,000 mm NTN
6008LLBNR deep groove ball bearings

Bearing No. 6008LLBNR

6008LLBNR Bearing 2D drawings and 3D CAD models

Size	40x68x15 mm
Bore Diameter	40,000 mm
Outer Diameter	68,000 mm
Width	15,000 mm
d	40,000 mm
D	68,000 mm
B	15,000 mm
C	15,000 mm
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.191
EAN	4547359547702
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	Yes
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Non-Contact Seal
Internal Clearance	C0-Medium
Inch - Metric	Metric



NTN DRIVESHAFT ANDERSON, INC.

Long Description	40MM Bore; 68MM Outside Diameter; 15MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; Yes Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.ntnamerica.com
Manufacturer Item Number	6008LLBNR/2A
Weight / LBS	0.423
Outer Race Width	0.591 Inch 15 Millimeter
Outside Diameter	2.677 Inch 68 Millimeter
Bore	1.575 Inch 40 Millimeter
bore diameter:	40 mm
precision rating:	ISO Class 0
outside diameter:	68 mm
finish/coating:	Uncoated
overall width:	15 mm
bearing material:	High Carbon Chrome Steel
bore type:	Round
cage material:	Steel
closure type:	Double Sealed
inner ring width:	15 mm
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	15 mm
snap ring included:	With Snap Ring
maximum rpm (grease):	10000 rpm
internal clearance:	CN



NTN DRIVESHAFT ANDERSON, INC.

fillet radius:	1 mm
operating temperature range:	-40 to 120 ° C
maximum rpm:	6100 RPM
dynamic load capacity:	16800 N
series:	60
static load capacity:	11500 N
manufacturer product page:	Click here