



# NTN DRIVESHAFT ANDERSON, INC.

## NTN 22317UAVS2 thrust roller bearings



Bearing No. 22317UAVS2

[22317UAVS2 Bearing 2D drawings and 3D CAD models](#)

Size	85x180x60 mm
Bore Diameter	85,000 mm
Outer Diameter	180,000 mm
Width	60,000 mm
d	85,000 mm
D	180,000 mm
H	60,000 mm
Category	Spherical Roller Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	7.34
EAN	4547359270587
Product Group	B04311
Internal Clearance	C0-Medium
Mounting Method	Shaft Mount
Rolling Element	Spherical Roller Bearing
Bore Profile	Straight
Cage Material	Bronze
Enclosure	Open
Number of Rows of Rollers	Double Row
Relubricatable	Yes
Withdrawal Sleeve	Not Applicable
Withdrawal Nut	Not Applicable
Inch - Metric	Metric
Long Description	85MM Straight Bore; 180MM Outside Diameter;



## NTN DRIVESHAFT ANDERSON, INC.

	60MM Width; C0-Medium Clearance; Shaft Mount; Double Row of Spherical Roller Bearings; Bronze Cage Material; Open Enclosure; Relubricatable
Category	Spherical Roller Bearing
UNSPSC	31171510
Harmonized Tariff Code	84823080
Noun	Bearing
Keyword String	Spherical
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
Weight / LBS	16.177
Outside Diameter	7.087 Inch   180 Millimeter
Adapter Part Number	Not Applicable Inch   Not Applicable Millimeter
Bore	3.346 Inch   85 Millimeter
Width	2.362 Inch   60 Millimeter
bore diameter:	85 mm
operating temperature range:	-40 to 120 ° C
outside diameter:	180 mm
cage material:	Brass
overall width:	60 mm
bearing material:	Through Hardened Steel
bore type:	Straight
cage type:	Machined
outer ring type:	Not Split
precision rating:	Not Rated
internal clearance:	Upper 2/3 of C4 range
finish/coating:	Uncoated
closure type:	Open
outer ring width:	60 mm
lubrication hole type:	Lubrication Groove & Hole



## NTN DRIVESHAFT ANDERSON, INC.

inner ring width:	60 mm
dynamic load capacity:	395000 N
fillet radius:	3 mm
static load capacity:	370000 N
series:	223
maximum rpm:	2300 rpm
manufacturer product page:	<a href="#">Click here</a>